

FLS-300

NETWORK TESTING—OPTICAL



- Multifunctional light source: up to three singlemode wavelengths on a single port, or four wavelengths (two multimode, and two singlemode) on two ports
- Power autonomy of 120 hours
- Highest output power in the industry
- Three-year warranty and recommended calibration interval, for dramatically reduced cost of ownership
- Ergonomic, eye-catching handheld package

The FLS-300 Light Source is part of EXFO's new line of handheld units, which includes the FPM-300 Power Meter and the FOT-300 Optical Loss Test Set.

Auto-Wavelength Recognition

The FLS-300 Light Source can transmit with a wavelength-identification digital encrypted protocol, so that any compatible unit—the FPM-300 Power Meter and the FOT-300 Optical Loss Test Set—can automatically use the proper calibration parameters. This feature reduces the need for communication between the two technicians and decreases the potential for error.

Distant Referencing

Signal encrypting can also give the receiving end information on the power to be used as reference, helping ensure efficient referencing, even when the two units are far apart.

FTTx Ready

EXFO's FLS-300 allows for the testing of passive optical networks (PONs) at 1310 nm, 1490 nm and 1550 nm, the three wavelengths recommended by the ITU-T (G.983.3) for PONs.



SPECIFICATIONS^a

Model ^b	23BL	234BL	235BL	12D	01-VCL
Central wavelength (nm)	1310 ± 20 1550 ± 20	1310 ± 20 1550 ± 20 1625 ± 15	1310 ± 20 1490 ± 10 1550 ± 20	850 ± 25 1300 +50/-10	850 ± 20
Spectral width ^c (nm)	≤ 5	≤ 5	≤ 5	50/135	≤ 1
Output power (dBm)	≥ 1/≥ 1	≥ 1/≥ -3/≥ -5	≥ 1/≥ -4.5/≥ -3	≥ -20/≥ -20 (62.5/125 μm)	≥ -3 (50/125 μm)
Power stability ^d (dB)					
8 hours	± 0.10	± 0.10	± 0.10	± 0.10	± 0.25
Battery life ^e (hours)	120	100	120	120	250
Enables automatic wavelength recognition	Yes	Yes	Yes	Yes	Yes
Tone generation (Hz)	270, 1 k, 2 k	270, 1 k, 2 k	270, 1 k, 2 k	270, 1 k, 2 k	270, 1 k, 2 k
Warranty and recommended calibration interval (years)	3	3	3	3	3

GENERAL SPECIFICATIONS

Size (H x W x D)	18.5 cm x 10.0 cm x 5.5 cm	(7 ¹ / ₄ in x 4 in x 2 ¹ / ₈ in)
Weight	0.4 kg	(0.9 lb)
Temperature	operating: -10 °C to 50 °C storage: -40 °C to 70 °C	(14 °F to 122 °F) (-40 °F to 158 °F)
Relative humidity	0 % to 95 % non-condensing	

STANDARD ACCESSORIES

User guide, Certificate of Calibration, instrument stickers in six languages, AC adapter, three AA batteries, wrist strap, alcohol cleaning pads.

SAFETY

21 CFR 1040.10 AND IEC 60825-1:1993+A1:1997+A2:2001:
CLASS 1 LASER PRODUCT

NOTES

- Guaranteed unless otherwise specified.
- All specifications valid at 23 °C ± 1 °C, with an FC connector.
- rms for lasers and -3 dB width for LEDs; typical values for LEDs.
- After 15 minutes warmup; expressed as ± half the difference between the maximum and minimum values measured during the period, with an APC connector on the power meter.
- Typical autonomy in Auto mode.

ORDERING INFORMATION

FLS-300-XX-XX

Model

FLS-300-01-VCL = 850 nm VCSEL 50/125 μm
 FLS-300-12D = 850/1300 nm LED 62.5/125 μm
 FLS-300-23BL = 1310/1550 nm laser 9/125 μm
 FLS-300-234BL = 1310/1550/1625 nm laser 9/125 μm
 FLS-300-235BL = 1310/1490/1550 nm laser 9/125 μm
 FLS-300-12D-23BL = 850/1300 nm LED 62.5/125 μm,
 1310/1550 nm laser 9/125 μm

Example: FLS-300-234BL-EI-EUI-89

Connector

EI-EUI-28 = UPC/DIN 47256
 EI-EUI-76 = UPC/HMS-10/AG
 EI-EUI-89 = UPC/FC narrow key
 EI-EUI-90 = UPC/ST
 EI-EUI-91 = UPC/SC
 EI-EUI-95 = UPC/E-2000

Rugged Handheld Solutions

OPTICAL	COPPER ACCESS
- OTDRs	- ADSL/ADSL2+, SHDSL, VDSL test sets
- OLTSs	- VoIP and IPTV test sets
- Power meters	- Ethernet test sets
- Light sources	- POTS test sets
- Talk sets	

Platform-Based Solutions

OPTICAL FIBER	DWDM TEST SYSTEMS	TRANSPORT AND DATA COM
- OTDRs	- OSAs	- Next Generation SONET/SDH and OTN testers
- OLTSs	- PMD analyzers	- SONET/DSn (DS0 to OC-192) testers
- DRL meters	- Chromatic dispersion analyzer	- SDH/PDH (64 kb/s to STM-64) testers
- Variable attenuators		- T1/T3, E1 testers
		- 10/100M and Gigabit Ethernet testers
		- Fibre Channel testers
		- 10 Gigabit Ethernet testers



根网通讯设备(北京)有限公司
 邮件: enquiry@rootscomm.com.cn
 网址: www.rootscomm.com.cn
 ROOTS Communication Equipment (Beijing) Co., Ltd.
 北京市朝阳区芳园西路5号 丽园中心508室 100015
 电话: +86-10-64382686
 传真: +86-10-64382703



Printed in Canada 06/12